

STD SILVER 15 - 1.52M

<https://www.motiva.ro/b2b/ro/folii-geamuri-301-ro/folii-geamuri-cladiri-213-ro/folii-protectie-solara-215-ro/std-silver-216-ro/std-silver-15-1.52m-801-ro.html>

Description

STD SILVER 15 – 1.52M, o folie metalizata, cu o durabilitate buna, asigura o respingere ridicata a caldurii si ofera intimitate excelenta din exterior. Folia ofera pana la 78% energie totala respinsa, 17% transparenta si aspect de oglinda puternic reflexiva din exterior.

GARANTIE:

- 10 ani - aplicate la interior in plan vertical
- 5 ani - aplicate la interior in plan inclinat sau orizontal

Specifications

CARACTERISTICI

Dimensiuni rola (I X L) m	1.52 X 30 m
Garantie	10 Ani

DATE TEHNICE

GROSIME FOLIE (1 MIL = 25 ?m)	2
% TRANSMISIA LUMINII VIZIBILE	17
% REFLECTANTA LUMINII VIZIBILE	61
% ENERGIE SOLARA TRANSMISA	11
% ENERGIE SOLARA REFLECTATA	57
% ENERGIE SOLARA ABSORBITA	32
COEFICIENTUL DE UMBRIRE	0.85
% ULTRAVIOLETE TRANSMISE	<1

% ENERGIE TOTALA RESPINSA	79
----------------------------------	-----------

EMISIVITATE	0.69
--------------------	-------------

GHID INSTALARE IN FUNCTIE DE VITRAJ

VITRAJ CU O SINGURA FOAIE DE STICLA	DA
--	-----------

VITRAJ CU DOUA FOI DE STICLA TRANSPARENTE	DA
--	-----------

VITRAJ CU DOUA FOI DE STICLA TRANSPARENTE + LOW-E	DA, S ? 1.5 mp
--	-------------------------------

VITRAJ CU DOUA FOI DE STICLA COLORATA	DA, S ? 1.5 mp
--	-------------------------------

VITRAJ CU DOUA FOI DE STICLA REFLEXIVE	DA, S ? 1.5 mp
---	-------------------------------

VITRAJ CU TREI FOI DE STICLA + LOW-E	NU
---	-----------